

INSPECTION SUPER SPYBALL CONTROL UNIT

Model SS-CPI for use with SSB-I Super Spyball

Portable Control Unit Model SS-CPI has been developed to complement the Inspection Super Spyball and make full use of its unique features.

Weighing only 11Kg and housed in a durable yellow Polypropylene case, this unit which operates from 100 to 240 volts AC, provides control, display, recording and video outputs from the Inspection Super Spyball.

The 15 inch TFT colour LCD display mounted in the case lid behind a scratch resistant Polycarbonate window displays a clear and bright image from the Spyball camera even in bright sunlight.

- Digital Video Recorder
- Record Still Photos during record or playback
- Video Text overlay using USB Keyboard
- Store unlimited pages of text for overlay
- Date and Time overlay
- Audio input for Microphone
- Built in audio playback speaker.
- Composite video output
- Joystick for proportional control of camera angle
- Option for GPS sensor and on screen position display



A Digital Video Recorder developed by Submertec saves up to 100 hours of best quality video and still photo files to the built in Solid State Drive with simultaneous export to USB memory. (up to 700 hours at lower quality)

DVR Menu controls are provided for playback, export from SSD, delete, file name, file number, record quality, date & time format etc. (menu displayed in English, French or Spanish)

Spyball control includes variable intensity LED lighting and laser Control.

Dedicated context sensitive menu display giving access to special functions such as invert joystick direction, set movement limits and display camera identification etc.

Panel facias are durable, wipe clean Polycarbonate membranes with control buttons and indicators clearly marked and logically grouped for ease of operation.

MODEL SS-CPI CONTROL UNIT SPECIFICATION

Dimensions	490mm wide, 394mm deep and 190mm high (when closed)
Weight	11Kg (24lb)
Power Supply	100 to 240 volts AC at 3 Amps
Display	15 inch sunlight viewable colour active matrix TFT LCD
Controls	Joystick, zoom, focus, lights, laser, DVR, Text & Display
DVR Files	Record AVI and JPG files to SSD and USB storage.
DVR Storage	Built in 240GB SSD. Option for larger capacity
Outputs	Composite video (PAL or NTSC) & Audio



Spyballs are available in a number of configurations and with control options to suit a range of tasks from inspection to aquaculture – please visit our web site at www.submertec.co.uk to view these together with other Submertec products.

Note: Specification may change without notice.